

tablemanager/includes/tables.inc

line 78

```
'#title' => t('Table Name'),
```

line 85

```
'#title' => t('Table Description'),
```

line 95

```
'#description' => t('Enter the number of columns you wish to have in your table.'),
```

line 164

```
'#title' => t('Default column to sort on?'),
```

line 114 and 356

```
'#options' => array('desc' => t('desc'), 'asc' => t('asc')),
```

tablemanager_admin/tablemanager_admin.module

line 188

```
'#options' => array(NULL => t('Show All'), 5 => '5', 10 => '10', 15 => '15', 25 => '25', 35 => '35', 50 => '50', 75 => '75', 100 => '100'),
```

line 214

```
$output .= "<table width='100%'><tr><td width='25%' align='left'><font size='+1'>. t('Viewing Table ').  
variable_get('tablemanager_table', '1') .:</font></td><td width='25%' align='center'>. l(t('Edit This Table'), 'admin/  
content/tablemanager/table_edit/table-').
```

That changing of font size is very distracting for the theme. I think, it's better to style it... for example, by class 'tableId' and define this class in tablemanager stylesheet (or anywhere):

line 214-217

```
$output .= "<table width='100%'><tr><td width='25%' align='left'><font size='+1'>. t('Viewing Table ').  
variable_get('tablemanager_table', '1') .:</font></td><td width='25%' align='center'>. l(t('Edit This Table'), 'admin/  
content/tablemanager/table_edit/table-'. variable_get('tablemanager_table', '1')) .<td width='25%' align='center'>. l(t  
(('Delete This Table'), 'admin/content/tablemanager/table_delete/table-'. variable_get('tablemanager_table',  
'1')) .</td>>";
```

```
$output .= "<td width='25%' align='right'>. l(t('Create New Table'), 'node/add/table') .</td></tr>";
```

```
$output .= "<tr><td colspan='4'><font size='+1'>. tablemanager_fetch_name(variable_get('tablemanager_table',  
'1')) .</font></td></tr></table>";
```

change to

```
$output .= "<table width='100%'><tr><td width='25%' align='left' class='tableId'>. t('Viewing Table '). variable_get  
(('tablemanager_table', '1') .</td><td width='25%' align='center'>. l(t('Edit This Table'), 'admin/content/  
tablemanager/table_edit/table-'. variable_get('tablemanager_table', '1')) .<td width='25%' align='center'>. l(t  
(('Delete This Table'), 'admin/content/tablemanager/table_delete/table-'. variable_get('tablemanager_table',  
'1')) .</td>>";
```

```
$output .= "<td width='25%' align='right'>. l(t('Create New Table'), 'node/add/table') .</td></tr>";
```

```
$output .= "<tr><td class='tableId' colspan='4'>. tablemanager_fetch_name(variable_get('tablemanager_table',  
'1')) .</td></tr></table>";
```

tablemanager/includes/settings.inc

line 18

```
'#options' => array(NULL => t('Display Nothing'), 'names' => t('Show Names'), 'table number' => t('Table  
Numbers')),
```

tablemanager/modules/tablemanager_list/tablemanager_list.module

line 121

```
$values = array(NULL => t('Show All'), 5 => '5', 10 => '10', 15 => '15', 25 => '25', 35 => '35', 50 => '50', 75 => '75',  
100 => '100');
```

line 133

```
'#options' => array('names' => t('Show Names'), 'table number' => t('Table Numbers')),
```

tablemanager/tablemanager.module

line 300-302

```
$perms[] = sprintf(t('create %s content'), check_plain($table['name']));
```

```
$perms[] = sprintf(t('edit any %s content'), check_plain($table['name']));
```

```
$perms[] = sprintf(t('edit own %s content'), check_plain($table['name']));
```

line 421

```
function tablemanager_display_new($tid, $list_length = NULL, $params = array()) {
```

```
  global $user, $pager_page_array, $pager_total_items, $pager_total;
```

```
  // check parameters are valid
```

```
  if (!$tid || !is_numeric($tid)) {
```

```
    return t('Invalid Table ID');
```

line 497

```
$name = t('Table '). $tid;  
break;  
case "names":  
    $name = $result->name == $tid ? t('Table '). $tid : check_plain($result->name);
```

line 563

```
if (!$header) {  
    return t('Invalid Table ID');
```

I don't know, how apply the translatable string below, but it can be done with additional variable (it works fine for me):

line 685

```
function tablemanager_load_tables() {  
    $tables = array();  
    $sql = db_query('SELECT tid, name FROM {tablemanager} ORDER BY tid');  
    while ($result = db_fetch_object($sql)) {  
        $tables[$result->tid] = $result->tid == $result->name ? "Table $result->tid" : "Table $result->tid: $result->name";
```

change to

```
function tablemanager_load_tables() {  
    $tables = array();  
    $sql = db_query('SELECT tid, name FROM {tablemanager} ORDER BY tid');  
    $tablelang = t('Table');  
    while ($result = db_fetch_object($sql)) {  
        $tables[$result->tid] = $result->tid == $result->name ? "$tablelang $result->tid" : "$tablelang $result->tid:  
$result->name";
```