Drupal 4.7 hook_nodeapi() Ops

8 July 2006

All hook_nodeapi() ops are executed immediately following the corresponding module hook, if it exists. For example, hook_nodeapi() is called with op 'insert' just after the node module's hook_insert() is called. Several ops (delete revision, prepare, submit) do not currently appear in the Drupal documentation. The documentation also lists an 'execute' op which is no longer valid. [http://api.drupal.org/api/4.7/function/hook_nodeapi] Here are the current ops and their additional arguments:

\$op	\$a3	\$a4	Description
delete	-	-	Node has just been deleted. Do additional DB queries if desired.
delete revision	-	-	A particular node revision has just been deleted. Do additional DB queries if desired.
insert	-	-	Node has just been created (node has nid). Do additional DB queries if desired.
load	_	-	Node is being loaded from the database. Add data by modifying the \$node object.
prepare	-	-	Node edit form is going to be shown, but \$node is not yet built (contains only a few uninteresting fields).
print	<pre>\$node->body</pre>	-	Node is going to be printed. This op is only executed if the book module is enabled. Modify \$node->body (not \$a3, which is extraneous) to create a printer friendly page.
search result	-	-	Node is about to be displayed as a search result. Return extra info which will appear in theme_search_item(\$item, \$type) as \$item['extra'].
submit	-	-	Node edit form has been submitted but node has not yet been inserted or updated.
update	_	-	Node has just been updated. Do additional DB queries if desired.
update index	_	-	Node is being indexed (for search). Return an array of additional strings (sentences) to be indexed.
validate	\$form	-	Node edit form has been submitted. Register errors with form_set_error(). The \$node cannot be modified.
view	\$teaser	\$page	Node is going to be displayed. Modify \$node->body or \$node->teaser if desired.